

## SOLID CORE PLYWOOD

High impact resistance due to its tensile strength, making it strong and stable when used as worktop. Good uniform strength and durability. Moderate water resistance. Ideal for mechanical workshops. Resin-based natural varnish ensures an impervious protective coating that is hardwearing and enhances the aesthetics at the same time. Comes in standard eased edge profile.



### TECHNICAL SPECIFICATIONS

- **Thickness:** 18mm, 25mm, 36mm, 50mm
- **Material:** Grade A solid core plywood
- **Finishing:** Natural varnishing
- **1 year** manufacturer warranty



Reverse Chamfer



Half Bullnose



Eased Edge

### MAINTENANCE & CARE GUIDELINES

Clean the surface just with a soft sponge or soft rag - (DO NOT use the abrasive "green" side of the sponge). Use common household cleaners without abrasives like detergent or window cleaner.

Always wipe dry with kitchen towel or dry cloth. Any prolonged exposure to liquids may damage or stain the worksurface.

We recommend instituting a regimen of monthly or quarterly inspections of all surfaces plus daily or weekly cleanings to maintain your worksurface's original finish and to help ensure a safe, uncontaminated working environment. The following list contains items you may wish to have on-hand for regular cleaning and to handle most problems that may occur.

- Clean rags or sponges (always use moist, not wet)
- Mild soap or household cleaners

Note: Never use wax or polish containing wax. Also never use abrasive pads, sponges, powders or liquids (such as Soft Scrub) as surface damage will occur.